Bollard Range Technical Information



...innovative carpark safety & traffic management solutions

Freecall

1800 polite (765 483)

Email

- ·

Web

www.polite.com.au

info@polite.com.au

Victoria (Head office)

Tel 03 9462 7400 Fax 03 9462 7411 274 Wolseley Place

THOMASTOWN VIC 3074 New South Wales

Tel 02 9831 2855 Fax 02 9831 2822 8/28 Garling Road KINGS

PARK NWS 2148 Queensland

Tel 07 3387 0160 Fax 07 3387 0159 3972 Pacific Hwy, LOGANHOLME QLD 4129

ACT, South Australia, Western

Australia, Northern Territory

Tel 1800 polite (765 483) Email info@polite.com.au



POLITE ENTERPRISES CORPORATION

Automatic Bollard Range



Product Description

Speed and durability

The rising or lowering time is about 3-4 seconds. All parts are protected against corrosion by aluminium oxide and powder coated. A rubber seal is fitted between the retractable bollard and the frame. All steel parts are protected against corrosion by aluminium oxide and powder coated. The internal parts are made of stainless steel or iron.

Installation

Foreign body ingress into the bollard is limited by a circular brush fastened to the cast-iron ground plate. As this does not make the bollard watertight, when installing bollards on an unprotected site, the frame should be connected to a sewage system (in this case, install a backflow stop valve). The post is raised by pneumatic power sized to suit the post type.





Key Features

Automatic Pneumatic control can control 1~3 bollards (optional)

Built to last

A highly rugged design for long life

Sturdy

Manufactured from corrosion-treated stainless steel (or iron optional)

High impact strength Height above ground: 600 mm

Low maintenance Yearly cleaning

Colours

With different colour highlight LED and glistening film (optional

VIC

P: +61 1800 765 483 264 274 Wolseley Place, THOMASTOWN VIC 3074

NSW

P: +61 1800 765 483 264 8/28 Garling Road KINGS PARK NSW 2148

OLD

P: +61 1800 765 483 264 16 7/3972 Pacific Highway, LOGANHOLME QLD 4129

SA. WA. TAS. NT

P: +61 1800 765 483 264



POLITE ENTERPRISES CORPORATION

Automatic Bollard Range

| SPECIFICATION | DBO-168P0 | DBO-168P4-1 | DBO-220P0 | DBO-220P4-1 |
|---------------------------|--|--|--|--|
| OPERATION UNIT | Pneumatic | Pneumatic | Pneumatic | Pneumatic |
| MATERIAL | Mild steel | 304 stainless steel | Mild steel | 304 stainless steel |
| SURFACE TREATMENT | Polishing | Polishing | Polishing | Polishing |
| WEIGHT KG | 75 | 75 | 115 | 115 |
| DIAMETER MM | 168 | 168 | 220 | 220 |
| POST LENGTH MM | 600 or 900 | 600 or 900 | 600 or 900 | 600 or 900 |
| UNDERGROUND LENGTH MM | 900 | 900 | 900 | 900 |
| OPERATION TIME | 3~5 seconds (adjustable) | 3~5 seconds (adjustable) | 3~5 seconds (adjustable) | 3~5 seconds (adjustable) |
| REFLECTIVE TAPE CM | 5 | 5 | 5 | 5 |
| WORKING NOISE | <60 db | <60 db | <60 db | <60 db |
| CONTROL LENGTH M | 50 | 50 | 50 | 50 |
| PIPELINE ACCESSORY M | 10 | 10 | 10 | 10 |
| WORKING VOLTAGE | AC240V | AC240V | AC240V | AC240V |
| WORKING CURRENT | <1.5A | <1.5A | <1.5A | <1.5A |
| WORKING TEMPERATURE | -5~70 ⁰ C | -5~70 ⁰ C | -5~70 ⁰ C | -5~70 ⁰ C |
| CONTROL BOX DBO-CP11 | control 1 bollard 740x520x720 60 kg |
| DBO-CP12 | control 2 bollards 790x590x850 (mm) 75 kg |
| DBO-CP13 | control 3 bollards 790x590x850 (mm) 75 kg |
| COLOUR OF REFLECTIVE TAPE | optional | optional | optional | optional |
| CONTROL LIGHT | optional | optional | optional | optional |



POLITE ENTERPRISES CORPORATION

Twist Lock Bollard Range




Product Description

Polite Enterprises Twist Locking Removable Bollards are designed to offer selective entry of vehicles into specific areas helping with security measures only allowing access to certain key holders. Polite Twist Locking Removable Bollards can be installed on various surfaces.

Chain rings with connecting chain can be installed into the bollards if this is a requirement for your bollards. Polite bollards come with all bolts and fixings needed for installation.

For softer surfaces such as asphalt our in ground bollards may be more suitable for your application and come with a fully welded starter bar where concrete feet will be installed.



Key Features

Durable

Manufactured from heavy durty, high strength, galvanised steel to prevent rust and corrosion

Visible

supplied with reflective striping to maximise deliniation and night visibility

Multiple Colors Stocked in standard safety yellow or white, but can be coated to the color of your choice

VIC

P: +61 1800 765 483 264 274 Wolseley Place, THOMASTOWN VIC 3074

NSW

P: +61 1800 765 483 264 8/28 Garling Road KINGS PARK NSW 2148

OL E

P: +61 1800 765 483 264 16 7/3972 Pacific Highway, LOGANHOLME QLD 4129

SA, WA, TAS, NT

P: +61 1800 765 483 264



POLITE ENTERPRISES CORPORATION

Twist Lock Bollard Range

| PRODUCT | PRODUCT CODE | MATERIAL | DIAMETER | WALL MM | WEIGHT KG | BASEPLATE | SIZE OF | NO. OF FIXINGS | HEIGHT | FOOTING | FOOTING |
|---------------------------------|-----------------|--------------------|--------------|------------|--------------|--------------|---------|-------------------|--------------------------|---------|---------|
| HEAVY DUTY ROUND BOLLARD | HRA-7TL | Mild steel | 165Ф | 5 | 28 | 300 | 16 | 4 | 1,200 above ground | 400 | 400 |
| | HRA-7TLFL | Mild steel | 140Ф | 5 | 28 | 300 | 16 | 4 | 1,200 above ground | 400 | 400 |
| | HRA-7TLSS | Stainless steel | 165Ф | 3.4 | 28 | 300 | 16 | 4 | 1,200 above ground | 400 | 400 |
| HEAVY DUTY SQUARE BOLLARD | HSA-3TL | Mild steel | 150 x 150 | 5 | 26 | 300 x 300 | 16 | 4 | 1,200 above ground | 400 | 400 |
| | HSA-3TLSS | Stainless steel | 150 x 150 | 3 | 26 | 300 x 300 | 16 | 4 | 1,200 above ground | 400 | 400 |
| | SRA-3TLSS | Mild steel | 165Ф | 5 | 28 | 300 | 16 | 4 | 1,200 above ground | 400 | 400 |
| STANDARD ROUND BOLLARD | SRA-5TL | Mild steel | 90Ф | 5 | 10 | 200 DIA | 12 | 4 | 1,000 above ground | 300 | 300 |
| | SRA-5TLSS | Stainless steel | 90Ф | 3 | 10 | 200 DIA | 12 | 4 | 1,000 above ground | 300 | 300 |
| STANDARD SQUARE BOLLARD | SSA-1TL | Stainless steel | 89 x 89 | 5 | 16 | 200 x 200 | 12 | 4 | 1,000 above ground | 300 | 300 |
| | SSA-1TLSS | Stainless steel | 89 x 89 | 3 | 16 | 200 x 200 | 12 | 4 | 1,000 above ground | 300 | 300 |



Top Locking Removable Bollard Range




TLB-2SS

Product Description

Polite Enterprises Top Locking Removable Bollards are designed to offer selective entry of vehicles into specific areas helping with security measures only allowing access to certain key holders. Polite Top Locking Bollards are designed to be able to be used in any location, and installed on various surfaces.

Polite Top Locking Bollards come with a top lock which uses an internal locking system that is not easily accessible without the use of power tools or the assigned key to the individual bollard. The base plated bollards are used and installed for use on suspended slabs. Option for in-ground Top Locking Bollards is also available through Polite. Chain rings with connecting chain can be installed into the bollards if this is a requirement for your bollards. Polite bollards come with all bolts and fixings needed for installation.



Key Features

Economical solutionProvides a medium to high security key lockable bollard without all the frills.

Reflective band

For superior night-time visibility

Heavy duty, high strength steel Using heavy, duty high strength steels make these bollards difficult to defeat.

Bollards available in standard colours of safety yellow or white, but can be custom

Lifting handle

For ease of transporting

P: +61 1800 765 483 264 274 Wolseley Place, **THOMASTOWN VIC 3074**

NSW

P: +61 1800 765 483 264 8/28 Garling Road **KINGS PARK NSW 2148**

P: +61 1800 765 483 264 16 7/3972 Pacific Highway, **LOGANHOLME QLD 4129**

SA, WA, TAS, NT

P: +61 1800 765 483 264



POLITE ENTERPRISES CORPORATION

Top Locking Removable Bollard Range

| PRODUCT | PRODUCT CODE | MATERIAL | DIAMETER | WALL | WEIGHT | BASEPLATE | SIZE OF FIXING MM | NO. OF FIXINGS | HEIGHT | FOOTING WIDTH MM | FOOTING DEPTH MM |
|------------------------|--------------|--------------------|----------|------|--------|-------------|----------------------|-------------------|--------------------------|---------------------|---------------------|
| TOP LOCKING BOLLARD | | Mild steel | 90Ф | 5 | 12 | - | - | - | 970 above ground | 300 x 300 | 500 |
| | | Stainless steel | 90Ф | 3.4 | 12 | - | - | - | 970 above ground | 300 x 300 | 500 |
| | | Mild steel | 90Ф | 5 | 12 | 280 CAST | 12 | 4 | 1,000 above ground | 300 x 300 | 400 |
| | | Stainless steel | 90Ф | 3.4 | 12 | 280 CAST | 12 | 4 | 1,000 above ground | 300 x 300 | 400 |
| | | Mild steel | 90Ф | 5 | 12 | - | - | - | 915 above ground | 300 x 300 | 1,200 |
| | | Mild steel | 90Ф | 5 | 10 | 200 | 12 | 4 | 970 above ground | - | - |
| FIXED BOLLARD | ILD IOO | Mild steel | 165Ф | 5 | 28 | 200 | 16 | 4 | 1,200 above ground | 400 x 400 | 400 |
| | ILD 0 | Mild steel | 90Ф | 5 | 10 | - | - | - | 1,000 above ground | 300 x 300 | 500 |
| | | Stainless steel | 90Ф | 3.4 | 10 | - | - | - | 1,000 above ground | 300 x 300 | 500 |



POLITE ENTERPRISES CORPORATION

Standard Bollard Range




Product Description

Polite Enterprises Standard Base Plate and In-ground Bollards are designed to be used in a variety of different applications including car parks and general factory settings.

Polite Bollards come in stainless steel or galvanized steel and can be powder coated in the standard safety yellow or white (additional colors available on request).

Chain rings with connecting chain can also be installed onto the bollards if this is a requirement of your individual application. Base plated bollards are best installed onto concrete surfaces, however, asphalt options are also available.



Key Features

- Durability: Manufactured from heavy duty,
 high strength galvanised steel or stainless steel
- •Visibility: Supplied with reflective striping to maximise delineation and night visibility
- •Cost Effectiveness
- Aesthetically Pleasing: Bollards are capped with either a dome or pyramid shaped cap

VIC

P: +61 1800 765 483 264 274 Wolseley Place, THOMASTOWN VIC 3074

NSW

P: +61 1800 765 483 264 8/28 Garling Road KINGS PARK NSW 2148

ם ום

P: +61 1800 765 483 264 16 7/3972 Pacific Highway, LOGANHOLME QLD 4129

SA, WA, TAS, NT

P: +61 1800 765 483 264



POLITE ENTERPRISES CORPORATION

Standard Bollard Range

| | PRODUCT CODE | MATERIAL | DIAMETER / SIZE MM | WALL MM | WEIGHT KG | BASE PLATE | SIZE OF FIXING | NO. OF FIXINGS | HEIGHT | FOOTING WIDTH | FOOTING DEPTH |
|-------------------------------|-----------------|--------------------|-----------------------|------------|--------------|---------------|-------------------|-------------------|--------------------------|------------------|------------------|
| STANDARD ROUND BOLLARD | SRA-5 | Mild steel | 90 Ф | 5 | 10 | 200 DIA | 12 | 4 | 1,025 above ground | 300 x 300 | 300 |
| | SRA-5SS | Stainless steel | 90 Ф | 3.4 | 10 | 200 DIA | 12 | 4 | 1,000 above ground | 300 x 300 | 300 |
| | | Mild steel | 90Ф | 5 | 10 | - | - | - | 1,000 above ground | 300 x 300 | 500 |
| | SRB-6SS | Stainless steel | 90Ф | 3.4 | 10 | - | - | - | 1,000 above ground | 300 x e 300 | 500 |
| STANDARD SQUARE BOLLARD | | | 89 x 89 | 5 | 16 | 200 x 200 | 12 | 4 | 1,000 above ground | 300 x 300 | 300 |
| | | | 89 x 89 | 3.4 | 16 | 200 x 200 | 12 | 4 | 1,000 above ground | 300 x 300 | 300 |
| | | | 89 x 89 | 5 | 17 | - | - | - | 1,000 above ground | 300 x 300 | 300 |
| | | | 89 x 89 | 3.4 | 17 | - | - | - | 1,000 above ground | 300 x 300 | 300 |



POLITE ENTERPRISES CORPORATION

Removable Bollard Range




Product Description

Polite Enterprises Corporation's Removable Bollards are designed to offer selective entry of vehicles into specific areas helping with security measures. Polite Removable Bollards are designed to be able to be used in any location and installed on any surface.

Polite Removable Base Plated Bollards are used and installed for use on a hard concrete surfaces. Options for in-ground Removable Bollards is also available through Polite.

Polite bollards come with all bolts and fixings needed for installation.

TLB-1SS TOP LOCKING BOLLARD 970 178-



Key Features

s are manufactured from heavy duty, high strength, sed steel to prevent rust and corrosion

supplied with reflective striping to maximise on and night visibility

le colours Is are stocked in standard colours of safety yellow or but can be coated to the colour of your choice

t effective
economy bollard range is an economical way to protect
lings, walls, equipment and roller doors
thetically pleasing Bollards are capped with either an
ctive pyramid shaped or dome shaped aluminium top

P: +61 1800 765 483 264 274 Wolseley Place, **THOMASTOWN VIC 3074**

P: +61 1800 765 483 264 8/28 Garling Road **KINGS PARK NSW 2148**

P: +61 1800 765 483 264 16 7/3972 Pacific Highway, **LOGANHOLME QLD 4129**

SA, WA, TAS, NT

P: +61 1800 765 483 264



POLITE ENTERPRISES CORPORATION

Removable Bollard Range

| PRODUCT | PRODUCT CODE | MATERIAL | DIAMETER / SIZE MM | WALL MM | WEIGHT KG | BASEPLATE | SIZE OF FIXING | NO. OF FIXINGS | HEIGHT | FOOTING WIDTH MM | FOOTING DEPTH MM |
|--|---------------|--------------------|-----------------------|---------|-----------|--------------|-------------------|-------------------|--------------------------|---------------------|---------------------|
| HEAVY DUTY REMOVABLE BOLLARD | HRRB-10-150 | Mild steel | 165 Ф | 5 | 28 | 300 | 16 | 4 | 1,200 above ground | 400 x 400 | 400 |
| STANDARD ROUND REMOVABLE BOLLARD | SRRB-10 | Mild steel | 90 Ф | 5 | 14 | - | - | - | 1,000 above ground | 300 x 300 | 500 |
| | SRRB-10-150SS | Mild steel | 165 Ф | 5 | 28 | 300 | 16 | 4 | 1,200 above ground | 400 x 400 | 400 |
| | SRRB-10SS | Stainless steel | 90 Ф | 3 | 14 | - | - | - | 1,000 above ground | 300 x 300 | 500 |
| STANDARD SQUARE REMOVABLE | SSRA-11 | Mild steel | 89 x 89 | 5 | 14 | 200 x 200 | 12 | 4 | 1,000 above ground | 300 x 300 | 300 |
| BOLLARD | SSRA-11SS | Stainless steel | 89 x 89 | 3 | 14 | 200 x 200 | 12 | 4 | 1,000 above ground | 300 x 300 | 300 |
| | SSRB-9 | Mild steel | 89 x 89 | 5 | 20 | - | - | - | 1,000 above ground | 300 x 300 | 500 |
| | SSRB-9SS | Stainless steel | 89 x 89 | 3 | 20 | - | - | - | 1,000 above ground | 300 x 300 | 500 |
| TOP LOCKING BOLLARD | TLB ECO-1 | Mild steel | 90 Ф | 5 | 11 | - | - | - | 900 above ground | 300 x 300 | 500 |
| | TLB ECO-2 | Mild steel | 90 Ф | 5 | 11 | 280 | 12 | 4 | 945 above ground | - | - |
| | TLB ECO-2SS | Stainless steel | 90 Ф | 3.4 | 11 | 28 0 | 12 | 4 | 945 above ground | - | - |
| | TLB-1 | Mild steel | 90 Ф | 5 | 12 | - | - | - | 970 above ground | 300 x 300 | 500 |
| | TLB-1SS | Stainless steel | 90 Ф | 3.4 | 12 | - | - | - | 970 above ground | 300 x 300 | 500 |
| | TLB-2 | Mild steel | 90 Ф | 5 | 12 | 280 CAST | 12 | 4 | 1,000 above ground | 300 x 300 | 400 |
| | TLB-2SS | Stainless steel | 90 Ф | 3.4 | 12 | 280 CAST | 12 | 4 | 1,000 above ground | 300 x 300 | 400 |



POLITE ENTERPRISES CORPORATION


In Ground Bollard Range



Product Description

Polite Enterprises In Ground Bollards are designed to be used in a variety of different applications including car parks and general factory settings. Polite Bollards come in stainless steel or galvanized steel and can be powder coated in the standard safety yellow or white (additional colors available on request).

Chain rings with connecting chain can also be installed onto the bollards if this is a requirement of your individual application. Base plated bollards are best installed onto concrete surfaces; in ground versions are available for other substrates. Polite bollards come in a square or round design and come with all bolts and fixings needed.



Key Features

rds are manufactured from heavy duty high strength nised steel to prevent rust and corrosion

supplied with reflective striping to maximise delineation

P: +61 1800 765 483 264 274 Wolseley Place, **THOMASTOWN VIC 3074**

P: +61 1800 765 483 264 8/28 Garling Road **KINGS PARK NSW 2148**

P: +61 1800 765 483 264 16 7/3972 Pacific Highway, **LOGANHOLME QLD 4129**

SA, WA, TAS, NT

P: +61 1800 765 483 264



POLITE ENTERPRISES CORPORATION

In Ground Bollard Range

| PRODUCT | PRODUCT | MATER | DIAMETER | WALL MM | WEIGHT KG | BASE PLATE | SIZE OF FIXING | NO.OF | HEIGHT | FOOTING WIDTH MM | FOOTING DEPTH MM |
|------------------------|---------------------|--------------------|--------------|------------|--------------|------------|-------------------|--------|-----------------------|---------------------|---------------------|
| | CODE | IAL | | IVIIVI | Itu | | FIXING | FIXING | | WIDTH MM | DEPTH MM |
| HEAVY DUTY ROUND | HRB-8 | Mild steel | 165 Φ | 5 | 32 | - | - | - | 1,200 above ground | 400 x 400 | 600 |
| BOLLARD | HRB-8SS | Stainless steel | 165 Ф | 3.4 | 32 | - | - | - | 1,200 above ground | 400 x 400 | 600 |
| HEAVY DUTY REMOVABLE | HRRB-8 | Mild steel | 165 Ф | 5 | 32 | - | - | - | 1,200 above ground | 400 x 400 | 400 |
| HEAVXRIDITY SQUARE | HSB-4 | Mild steel | 150 x 150 | 5 | 34 | - | - | - | 1,200 above ground | 400 x 400 | 600 |
| BOLLARD | HSB-4SS | Stainless steel | 150 x 150 | 3 | 34 | - | - | - | 1,200 above ground | 400 x 400 | 600 |
| STANDARD ROUND | SRB-6 | Mild steel | 90 Ф | 5 | 10 | - | - | - | 1,000 above ground | 300 x 300 | 500 |
| BOLLARD | SRB-6SS | Stainless steel | 90 Ф | 3 | 10 | _ | - | - | 1,000 above ground | 300 x 300 | 500 |
| STANDARD ROUND | SRRB-10 | Mild steel | 90 Ф | 5 | 14 | - | - | _ | 1,000 above ground | 300 x 300 | 500 |
| REMOVABLE BOLLARD | SRRB-10-150FL | Mild steel | 165 Ф | 5 | 32 | - | - | - | 1,200 above ground | 400 x 400 | 400 |
| STANDARD ROUND | SRRB-10-150SS | Mild steel | 165 Ф | 5 | 32 | - | - | - | 1,200 above ground | 400 x 400 | 400 |
| REMOVABLE BOLLARD | SRRB-10FL | Mild steel | 90 Ф | 5 | 14 | - | - | - | 1,000 above ground | 300 x 300 | 500 |
| | SRRB-10SS | Stainless steel | 90 Ф | 3 | 14 | - | - | - | 1,000 above ground | 300 x 300 | 500 |
| STANDARD SQUARE | SSB-2 | Mild steel | 89 x 89 | 5 | 17 | - | - | - | 1,000 above ground | 300 x 300 | 300 |
| BOLLARD | SSB-2SS | Stainless steel | 100 x 100 | 3 | 17 | - | - | - | 1,000 above ground | 300 x 300 | 300 |
| STANDARD SQUARE | SSCB-13 | Mild steel | 89 x 89 | 5 | 13 | - | - | - | 800 above ground | 300 x 300 | 500 |
| COLLAPSIBLE BOLLARD | SSCB-13SS | Stainless steel | 100 x 100 | 3 | 13 | - | - | - | 800 above ground | 300 x 300 | 500 |
| TOP LOCKING BOLLARD | TLB ECO-1 | Mild steel | 90 Ф | 5 | 11 | - | - | - | 900 above ground | 300 x 300 | 500 |
| | TLB ECO-1SS | Stainless steel | 90 Ф | 3 | 11 | - | - | - | 900 above ground | 300 x 300 | 500 |
| HEAVY DUTY ROUND | TLB ECO-5 | Mild steel | 90 Ф | 5 | 10 | - | - | - | 1,000 above ground | 300 x 300 | 500 |
| BOLLARD | TLB ECO-5SS | Stainless steel | 90 Ф | 3.4 | 10 | - | <u>-</u> | - | 1,000 above ground | 300 x 300 | 500 |
| TOP LOCKING BOLLARD | TLB -1 | Mild steel | 90 Ф | 5 | 12 | - | | - | 970 above ground | 300 x 300 | 500 |
| | TLB-1 SS | Stainless steel | 90 Ф | 3.4 | 12 | - | - | - | 970 above ground | 300 x 300 | 500 |
| | TLB -3 | Mild steel | 90 Ф | 5 | 12 | - | - | - | 915 above ground | 300 x 300 | 1,200 |
| | TLB-3 SS | Stainless steel | 90 Ф | 3.4 | 12 | - | - | - | 915 above ground | 300 x 300 | 1,200 |
| FIXED BOLLARD | TLB-5 | Mild steel | 90 Ф | 5 | 10 | - | - | - | 1,000 above ground | 300 x 300 | 500 |
| | TLB-5 _{SS} | Stainless steel | 90 Ф | 3.4 | 10 | _ | _ | - | 1,000 above ground | 300 x 300 | 500 |



POLITE ENTERPRISES CORPORATION

Heavy Duty Bollard Range



Product Description


Heavy duty Base Plated Bollards are designed to be used in a variety of different applications within car parks and general settings where bollards are required to protect pedestrians or property.

Heavy duty bollards are manufactured in 165mm diameter or 150mm square versions (other sizes available on request) and are available in standard powder coated yellow or white. Stainless steel and hot dipped galvanized versions are also available.

Heavy Duty bollards are supplied with a domed chrome top for added aesthetics or are available in flat or standard dome lid versions

Base plated bollards are designed for fixing directly to concrete surfaces. In ground versions are available for other substrates.





KEY FEATURES

Durable

Manufactured from heavy duty, high strength, galvanised steel to prevent rust and corrosion

Cost effective

Our economy bollard range is an economical way to protect buildings, walls, equipment and roller doors

Visible

Supplied with reflective striping to maximise delineation and night visibility

Aesthetically pleasing Bollards are capped with either an attractive pyramid shaped or dome shaped top

Multiple colours Stocked in standard safety yellow or white, but can be coated to the colour of your choice

VIC

P: +61 1800 765 483 264 274 Wolseley Place, THOMASTOWN VIC 3074

NSW

P: +61 1800 765 483 264 8/28 Garling Road KINGS PARK NSW 2148

QLD

P: +61 1800 765 483 264 16 7/3972 Pacific Highway, LOGANHOLME QLD 4129

SA, WA, TAS, NT

P: +61 1800 765 483 264



POLITE ENTERPRISES CORPORATION

Heavy Duty Bollard Range

| PRODUCT | PRODUCT CODE | MATERIAL | DIAMETER / SIZE MM | WALL | WEIGHT KG | BASEPLATE | SIZE OF FIXING MM | NO. OF FIXINGS | HEIGHT | FOOTING WIDTH MM | FOOTING DEPTH MM |
|---------------------------------|-----------------|--------------------|-----------------------|------|-----------|-----------|----------------------|-------------------|--------------------------|---------------------|---------------------|
| HEAVY DUTY ROUND BOLLARD | HRA-7 | Mild steel | 165 Ф | 5 | 28 | 300 | 16 | 4 | 1,200 above ground | 400 x 400 | 400 |
| | HRA-7SS | Stainless steel | 165 Ф | 3.4 | 28 | 300 | 16 | 4 | 1,200 above ground | 400 x 400 | 400 |
| | | Mild steel | 165 Ф | 5 | 32 | - | - | - | 1,200 above ground | 400 x 400 | 600 |
| | HRB-8SS | Stainless steel | 165 Ф | 3.4 | 32 | - | - | - | 1,200 above ground | 400 x 400 | 600 |
| HEAVY DUTY SQUARE BOLLARD | | Mild steel | 150 x 150 | 5 | 26 | 300 | 16 | 4 | 1,200 above ground | 400 x 400 | 400 |
| | HSA-3SS | Stainless steel | 150 x 150 | 3 | 26 | 300 | 16 | 4 | 1,200 above ground | 400 x 400 | 400 |
| | | Mild steel | 150 x 150 | 5 | 34 | - | - | - | 1,200 above ground | 400 x 400 | 600 |
| | HSB-4SS | Stainless steel | 150 x 150 | 3 | 34 | - | - | - | 1,200 above ground | 400 x 400 | 600 |



POLITE ENTERPRISES CORPORATION

Flexible Bollard Range



Product Description

Polite Flexi bollards are designed to flex in any direction when impacted to minimize damage to vehicles. Designed specifically to be able be used where motor vehicles are maneuvering at low speeds such as car parking spaces etc. Being flexible, costly replacements are reduced as impact is less damaging to the bollard.

Polite Flexible Bollards look like ordinary steel to the untrained eye but are equipped with a unique polymer rubber insert allowing the bollard to flex up to a 45 degree angle.

Base plated bollards are designed for fixing directly to concrete surface. In ground versions are available for other substrates.

Flexible bollards are available in standard (90mm diameter) and Heavy duty (165mm diameter) models and are powder coated yellow. (custom colors available on request). Stainless steel 304 or 316 versions are also available.



Key Features

Made from long-life polyurethane material with exceptional vertical rebound resilience, tensile strength and impact resistance

Bright fluorescent yellow colour with high intensity, reflective banding ensures high visibility day and night

Incorporating 'vertical memory' for the fast recovery of the bollard no matter how many

Versatility Available in two sizes, 750 mm and 450 mm, addressing all likely requirements by simply bolting down to the existing road surface

VIC

P: +61 1800 765 483 264 274 Wolseley Place, **THOMASTOWN VIC 3074**

P: +61 1800 765 483 264 8/28 Garling Road **KINGS PARK NSW 2148**

P: +61 1800 765 483 264 16 7/3972 Pacific Highway, **LOGANHOLME QLD 4129**

SA, WA, TAS, NT

P: +61 1800 765 483 264



POLITE ENTERPRISES CORPORATION

Flexible Bollard Range

| PRODUCT | PRODUCT CODE | MATERIAL | DIAMETER | WALL | WEIGHT | BASEPLATE | SIZE OF FIXING MM | NO. OF FIXINGS | HEIGHT | FOOTING WIDTH MM | FOOTING DEPTH MM |
|---|---------------|--------------------|----------|------|--------|-----------|----------------------|-------------------|--------------------------|---------------------|---------------------|
| HEAVY DUTY ROUND BOLLARD | HRA-7FL | Mild steel | 140 Ф | 5 | 28 | 300 | 16 | 4 | 1,200 above ground | 400 x 400 | 400 |
| | HRA-7TLSS | Stainless steel | 165 Ф | 3.4 | 28 | 300 | 16 | 4 | 1,200 above ground | 400 x 400 | 400 |
| | HRB-8FL | Mild steel | 140 Ф | 5 | 32 | - | - | - | 1,200 above ground | 400 x 400 | 600 |
| STANDARD ROUND BOLLARD | HRB-8SSFL | Stainless steel | 140 Ф | 3.4 | 32 | - | - | - | 1,200 above ground | 400 x 400 | 600 |
| | SRA-5FL | Mild steel | 90 Ф | 5 | 10 | 200 | 12 | 4 | 1,000 above ground | 300 x 300 | 300 |
| | SRA-5SS | Stainless steel | 90 Ф | 3 | 10 | 200 | 12 | 4 | 1,000 above ground | 300 x 300 | 300 |
| | SRA-5FLSS | Stainless steel | 90 Ф | 3 | 10 | 200 | 12 | 4 | 1,000 above ground | 300 x 300 | 300 |
| | SRB-6FL | Mild steel | 90 Ф | 5 | 10 | - | - | - | 1,000 above ground | 300 x 300 | 500 |
| | SRB-6FLSS | Stainless steel | 90 Ф | 3 | 10 | - | - | - | 1,000 above ground | 300 x 300 | 500 |
| STANDARD ROUND REMOVABLE BOLLARD | SRRB-10-150FL | Mild steel | 165 Ф | 5 | 28 | 300 | 16 | 4 | 1,200 above ground | 400 x 400 | 400 |
| BOLLAND | SRRB-10FL | Mild steel | 90 Ф | 5 | 14 | - | - | - | 1,000 above ground | 300 x 300 | 500 |



POLITE ENTERPRISES CORPORATION

Collapsible Bollard Range







Product Description

Depending on your surface will depend on the right type of application for the bollard. Polite Bollards come in galvanized steel or they can be powder coated yellow or white (additional colors available).

Polite Collapsible bollards are designed for vehicle access control. With an easy lockable system these bollards can easily be folded down and returned back up when needed in a matter of seconds. Polite Bollards are made from a high quality heavy duty steal and come with necessary fixings.





Key Features

Compact

35 mm when lowered, eliminating possible damage to the vehicle undercarriage

Maintenance free

Corrosive free; zinc plated and powder coated finish

Cost efficient

The most cost effective way to protect private or reserved parking bays

Easy to install

Simply bolt to the existing surface or in ground

Easy to use

Simply unlock and lay flat to gain or restrict access

Locks up and down

To prevent unauthorised use

VIC

P: +61 1800 765 483 264 274 Wolseley Place, THOMASTOWN VIC 3074

NSV

P: +61 1800 765 483 264 8/28 Garling Road KINGS PARK NSW 2148

OLD

P: +61 1800 765 483 264 16 7/3972 Pacific Highway, LOGANHOLME QLD 4129

SA, WA, TAS, NT

P: +61 1800 765 483 264



POLITE ENTERPRISES CORPORATION

Collapsible Bollard Range

| PRODUCT | PRODUCT CODE | MATERIAL | SIZE MM | WALL MM | WEIGHT KG | l | SIZE OF FIXINGS | NO. OF FIXINGS | HEIGHT MM | FOOTING WIDTH MM | FOOTING DEPTH MM |
|--|-----------------|---------------|------------|---------|-----------|---------------------|--------------------|-------------------|------------------------|---------------------|---------------------|
| STANDARD SQUARE COLLAPSIBLE BOLLARD | SSCA-12 | Mild steel | 89 x 89 | 5 | 14 | 200 x 200 | 12 | 4 | 800 Above Ground | 300 x 300 | 300 |
| | SSCB-13 | Mild steel | 89 x 89 | 5 | 13 | In Ground Sleeve | - | - | 800 Above Ground | 300 x 300 | 500 |



POLITE ENTERPRISES

Base Plate Bollard Range



Product Description

Polite Enterprises Base Plated Bollards are designed to be used in a variety of different applications including car parks and general factory settings.

Polite Bollards come in stainless steel or galvanised steel and can be powder coated in the standard safety yellow or white (additional colors available on request).

Chain rings with connecting chain can also be installed onto the bollards if this is a requirement of your individual application. Base plated bollards are best installed onto concrete surfaces.

Polite bollards come in a square or round design and come with all bolts and fixings needed.



KEY FEATURES

InstallationAll bollards are supplied with a 10 mm thick baseplate ready to fix to existing surface

DurableBollards are manufactured from heavy duty, high strength galvanised steel to prevent rust and

VisibleAll bollards are supplied with reflective striping to maximise delineation and night-time visibility

Bollards are stocked in standard colours of safety yellow or white, but can be coated to the colour of your choice

Cost effective
Our economy bollard range is an economical way
to protect buildings, walls, equipment and roller

Aesthetically pleasing Bollards are capped with either an attractive pyramid shaped or dome shaped aluminium top

Contact



POLITE ENTERPRISES CORPORATION


Base Plate Bollard Range

| THODOOT | PRODUCT M | MATERIAL D Si | IAMETER / | WALL MM | WEIGHT KG | BASEPLATE MM | SIZE OF FIXING MM | NO. OF FIXINGS | | FOOTING WIDTH MM | FOOTING DEPTH MM |
|--|-------------|--------------------|-----------|---------|-----------|-----------------|----------------------|-------------------|-----------------------|---------------------|---------------------|
| HEAVY DUTY ROUND BOLLARD | HRA-7 | Mild steel | 165 | 5 | 28 | 300Ф | 16 | 4 | 1,200 above ground | 400 x 400 | 400 |
| | HRA-7FL | Mild steel | 140 | 5 | 32 | 300Ф | 16 | 4 | 1,200 above ground | 400 x 400 | 400 |
| | HRA-7SS | Stainless steel | 165 | 3.4 | 28 | 300Ф | 16 | 4 | 1,200 above ground | 400 x 400 | 400 |
| HEAVY DUTY SQUARE BOLLARD | HSA-3 | Mild steel | 150 x 150 | 5 | 26 | 300 x 300 | 16 | 4 | 1,200 above ground | 400 x 400 | 400 |
| | HSA-3SS | Stainless steel | 150 x 150 | 3 | 26 | 300 x 300 | 16 | 4 | 1,200 above ground | 400 x 400 | 400 |
| STANDARD ROUND BOLLARD | SRA-5 | Mild steel | 90 | 5 | 10 | 200Ф | 12 | 4 | 1,200 above ground | 300 x 300 | 300 |
| HEAVY DUTY SQUARE BOLLARD | HSB-4SS | Stainless steel | 150 x 150 | 3.4 | 34 | - | - | - | 1,200 above ground | 400 x 400 | 600 |
| STANDARD ROUND BOLLARD | SRA-5SS | Stainless steel | 90 | 3.4 | 10 | 200Ф | 12 | 4 | 1,000 above ground | 300 x 300 | 300 |
| STANDARD SQUARE BOLLARD | SSA-1 | Mild steel | 89 x 89 | 5 | 16 | 200 x 200 | 12 | 4 | 1,000 above ground | 300 x 300 | 300 |
| | SSA-1SS | Stainless steel | 89 x 89 | 3 | 16 | 200 x 200 | 12 | 4 | 1,000 above ground | 300 x 300 | 300 |
| STANDARD SQUARE COLLAPSIBLE BOLLARD | SSCA-12 | Mild steel | 89 x 89 | 5 | 14 | 200 x 200 | 12 | 4 | 800 above ground | 300 x 300 | 300 |
| STANDARD SQUARE COLLAPSIBLE BOLLARD | SSCA-12SS | Stainless steel | 89 x 89 | 3.4 | 14 | 200 x 200 | 12 | 4 | 800 above ground | 300 x 300 | 300 |
| STANDARD SQUARE REMOVABLE BOLLARD | SSRA-11 | Mild steel | 89 x 89 | 5 | 14 | 200 x 200 | 12 | 4 | 1,000 above ground | 300 x 300 | 300 |
| | SSRA-11SS | Stainless steel | 100 x 100 | 3.4 | 14 | 200 x 200 | 12 | 4 | 1,000 above ground | 300 x 300 | 300 |
| TOP LOCKING BOLLARD | TLB ECO-2 | Mild steel | 90Ф | 5 | 11 | 280 | 12 | 4 | 945 above ground | - | - |
| | TLB ECO-2SS | Stainless steel | 90Ф | 3.4 | 11 | 280 | 12 | 4 | 945 above ground | - | - |
| | TLB ECO-4 | Mild steel | 90Ф | 5 | 10 | 200 | 12 | 4 | 930 above ground | - | - |
| | TLB ECO-4SS | Stainless | 90Ф | 3.4 | 10 | 200 | 12 | 4 | 930 above ground | - | - |
| | TLB-2 | Mild steel | 90Ф | 5 | 12 | 280 CAST | 12 | 4 | 1,000 above ground | 300 x 300 | 400 |
| | TLB-2SS | Stainless steel | 90Ф | 3.4 | 12 | 280 CAST | 12 | 4 | 1,000 above ground | 300 x 300 | 400 |
| | TLB-4 | Mild steel | 90Ф | 5 | 10 | 200 | 12 | 4 | 970 above ground | - | - |
| FIXED BOLLARD | TLB-4SS | Stainless steel | 90Ф | 5 | 10 | 200 | 12 | 4 | 970 above ground | - | - |



Platinum Range Semi-Automatic Retractable Bollard

Semi-automatic bollards are a fantastic solution for high security areas with limited access control requirements. As safety requirements increase the cylinder size becomes bigger allowing the built-in pressure assistant system to take an increased load. These bollards have a recommended maximum spacing of 1.4m and excavation depth of 30cm.



Key features

- high level security
- easy operation
- various styles available to suit different
- architecture environments
- unified with other bollards in range



SPECIFICATIONS


HEIGHT
DIAMETER OPTIONS
220mmmaterial options
PART NUMBERS

900mm
114mm, 133mm, 168mm,
Galvanised Steel, Stainless Steel
Galv. 114mm | DBO114SO900
Galv. 133mm | DBO133SO900
Galv. 168mm | DBO168SO900
Galv. 220mm | DBO220SO900
Stainless 114mm | DBO114S4900
Stainless 133mm | DBO133S4900

Stainless 220mm | DBO220S4900

Platinum Range Retractable Bollard

Easily the best solution for private car parks and garages, retractable bollards provide a practical and convenient solution in most environments. Retractable bollards provide great protection from unwanted vehicles with minimal effort. These bollards have a recommended maximum spacing of 1.4m and excavation depth of 30cm.



Key features

- traffic control
- landscape design
- permanent access control
- perimeter control
- various styles available to suit different
- architecture environments
- unified with other bollards in range



SPECIFICATIONS

HEIGHT
DIAMETER OPTIONS
MATERIAL OPTIONS
PART NUMBERS

900mm 90mm, 114mm, 133mm Galvanised Steel, Stainless Steel Galv. 90mm | DBO89R0-900 Galv. 114mm | DBO114R0900 Galv. 133mm | DBO133R0900 Stainless 90mm | DBO89R4900 Stainless 114mm | DBO114R4900 Stainless 133mm | DBO133R4900



Platinum Range Automatic Retractable Bollard

Automatic bollards are quickly becoming a more secure alternative to boom gates. Designed and manufactured by Polite Enterprises Corporation (PEC), the automatic retractable bollard provides access control and complete site security unlike boom gates, which can be damage d or easily defeated.



Key features

- Manufactured from stainless steel
- or galvanised steel (powder coated)
- Automatic pneumatic control
- · Very high impact strength
- Height above ground: 900mm
- LED colour high light and glistening film
- (optional)
- Control box can control 1 3 bollards
- Fully assembled power and control units
- Easy maintenance
- Fast responding speeds, enabling rapid
- direction changes



SPECIFICATIONS

HEIGHT
DIAMETER OPTIONS
MATERIAL OPTIONS
OPERATING TIME
WORKING NOISE
REFLECTIVE TAPE
LED COLOR
PROTECTION LEVEL
WORKING CURRENT

PART NUMBERS

900mm

168mm, 220mm, 275mm

Galvanised Steel, Stainless Steel

3-5 seconds (adjustable)

<60db 5cm Optional

IP67 <1.5A

BOL AUTO